

#### Hefei TNJ Chemical Industry Co.,Ltd.

B911 Xincheng Business Center, Qianshan Rd. Hefei 230022 China

Tel: (0086) 551 65418678
Fax: (0086) 551 65418697
Email: info@tnjchem.com
Site: www.tnjchem.com

# Technical Data Sheet

## Benzyl benzoate

Chemical Name Benzyl benzoate

CAS # 120-51-4
EINECS 204-402-9
Formula C14H12O2
Molecular Weight 212.24

Synonyms Benzyl alcohol benzoic ester

**Chemical Structure** 

Appearance Colorless or pale yellow viscous transparent liquid

## Description

**Benzyl benzoate CAS 120-51-4** is a colorless or pale yellow viscous transparent liquid. In te mperature conditions of 17 degrees centigrade or lower, it will be solidified into white solid. Be nzyl benzoate of high-purity has slight fragrance. Benzyl benzoate is insoluble in water but sol uble in organic solvents. Benzyl benzoate is a hightemperature solvent, is the only solvent of Musk. Benzyl benzoate has applications to pharmacy and perfume industryjust because of its characters of low volatilization and relative stability.

#### **Specification**

ItemBP2000Perfumery GradeAppearanceyellow transparent liquidcolorless transparent liquidFragrance--light scent of flower

Acidity(ml,0.1N NaOH 2.0g)       ≤0.2       ≤0.2         Specific Gravity20 °C,kg/ m3       1118—1122       1118—1122         Refractive Index(nD20)       1.568—1.570       1.568—1.570         Freezing Point (°C)       ≥17.0       ≥17.0         Moisture (%)       ≤0.3       ≤0.2
Refractive Index(nD20)       1.568—1.570       1.568—1.570         Freezing Point (°C)       ≥17.0       ≥17.0
Freezing Point (°C) ≥17.0 ≥17.0
Moisture (%) ≤0.3 ≤0.2
Sulphate Ash (%) ≤0.1 ≤0.2

#### **Application**

- 1) Benzyl benzoate is mainly used in the area of textile auxiliary, fragrance and flavor, pharmacy, plasticizer etc.
- 2) For its good performance of plasticity, solvent, safety and environmental protection, benzyl benzoate has been widely used into synthesis of lead agent, leveling agent, repair agent etc.

### **Packing**

225kg per iron drum,80drum per 20"container; 25kg/plastic drum.

#### Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchant ability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if we has been advised of the possibility of such damages.

#### Hefei TNJ Chemical Industry Co.,Ltd.

B911 Xincheng Business Center

Tel: (0086) 551 5418695

Qianshan Road, Hefei

Fax: (0086) 551 5418697

230022 Anhui

Email: info@tnjchem.com

China

Site: www.tnjchem.com